

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International publication date
4 August 2005 (04.08.2005)

PCT

(10) International publication number
WO 2005/071342 A1


- (51) International patent classification⁷: F28D 9/00 [DE/DE]; Wäldenbronnerstrasse 2/6, 73732 Esslingen (DE). RICHTER, Jens [DE/DE]; Benzenmühle 1, 71723 Grossbottwar (DE).
- (21) International application number: PCT/EP2004/013828
- (22) International filing date: 6 December 2004 (06.12.2004)
- (25) Language of filing: German
- (26) Language of publication: German
- (30) Data relating to the priority: 10 2004 003 790.6 23 January 2004 (23.01.2004) DE
- (71) Applicant (for all designated States except US): BEHR GMBH & CO. KG [DE/DE]; Mauserstrasse 3, 70469 Stuttgart (DE).
- (72) Inventors; and
- (75) Inventors/Applicants (US only): KÖBLIN, Rüdiger
- (74) Joint Representative: BEHR GMBH & CO. KG; Intellectual Property, G-IP, Mauserstrasse 3, 70469 Stuttgart (DE).
- (81) Designated states (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[continued on next page]

As printed

(54) Title: HEAT EXCHANGER, ESPECIALLY OIL/COOLANT COOLER

(54) Bezeichnung: WÄRMETAUSCHER, INSBESONDERE ÖL-/KÜHLMITTEL-KÜHLER



(57) Abstract: The invention relates to a heat exchanger, especially a stacked plate oil cooler (1) having a plate-type design. The heat exchanger is characterized in that two adjacent heat exchanger plates (2) define a space between them through which the heat exchange medium or a second medium that is to be cooled or heated flows. At one end of said heat exchanger, a base plate (3) lies substantially flat against the adjacent outmost heat exchanger plate (2) of the heat exchanger. Said base plate (3) is provided with a recess (5) whose contour follows that of the heat exchanger plate (2).

[continued on next page]

(84) **Designated states** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *With International Search Report.*

For an explanation of the two-letter codes and the other abbreviations, reference is made to the explanations ("Guidance Notes on Codes and Abbreviations") at the beginning of each regular edition of the PCT Gazette.

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for the following designation US*

BEST AVAILABLE COPY

(57) **Zusammenfassung:** Die Erfindung betrifft einen Wärmetauscher, insbesondere einen Stapelscheiben-Ölkühler (1), in Scheibenhauweise, wobei zwei benachbarte Wärmetauscherplatten (2) einen Zwischenraum definieren, der von einem Wärmetauschermedium oder einem zu kühlenden oder zu erwärmenden zweiten Medium durchströmt ist, und an einem Ende eine Grundplatte (3) vorgesehen ist, die in zumindest im Wesentlichen flächiger Anlage an die benachbarte äußerste Wärmetauscherplatte (2) des Wärmetauschers ist. Dabei weist die Grundplatte (3) eine Vertiefung (3) mit einer der Wärmetauscherplatte (2) entsprechend verlaufenden Kontur auf.